

February 09, 2010

This report represents a preliminary determination of project requirements from various city departments based on project characteristics that you identified on the Site Plan and the Preliminary Application Form and also on your pre-application site visit (PASV). The city's goal is to provide you with as much information and assistance as possible prior to your permit application submittal. Complete and accurate application materials help to reduce the need for correction cycles that delay permit approval. This coordinated list of requirements and decisions has been created for you to use as reference for creating a more complete submittal package. The information in this report can also be utilized if you need to develop a street improvement plan (SIP) for submittal to SDOT for SIP Design Guidance and 90% completed SIP acceptance (see SDOT CAM 2200, 2201, 2211, 2212, 2213, and 2214).

PASV report requirements may be subject to additions, changes, or modifications by the department. The purpose of the report is to alert the applicant that there may be unusual or complex site conditions that trigger requirements from the department regarding this project. The applicant is responsible for providing all required documents at the intake appointment. If you have questions about this report or PASV process, please contact the DPD Site Development Team at (206) 684-8860.

Note: A preliminary assessment is being conducted on all land use projects as well as new free-standing buildings (new construction). If you have a building project associated with your land use project, the preliminary assessment will not be repeated on the building project.

The applicant assumes full responsibility for determining all permit requirements and infrastructure improvements per applicable sections of the Seattle Municipal Code and the City of Seattle's Right-of-Way Improvement manual.

- If an SIP is required, SDOT must accept your 90% complete SIP before DPD construction intake (see CAM 2200, 2206, 2209, 2211, 2213, and 2214).
- If street improvements are required, you must obtain all necessary permits from SDOT.
- Street use permits are required for all work in the right-of-way (see SDOT CAM 2100).

Project Summary			
AP/Project No.	6238614	Ground Disturbance	Υ
Application Template	BLDG	PASV Required This Permit	Υ
Application Type	CONSTRUCTION AND DEVELOPMENT	Date PASV Completed	01/26/10
Category	COMMERCIAL	PASV Done Under	
DPD Review Type	FULL	Permit Remarks	
Address	2510 NE Blakeley St		
Location			
Zoning		Applicant	JERRY ISAKSEN 4545 S UNION AVE SUITE 200 TACOMA W 98409 (253) 475-0380
King County APN	9191201680		
Permit Status	Initial Information Collected		
	Demolition of existing structure & construction of a new 2-story, 6,400 +/ SF office building. Note: Site impervious area shall be reduced.	Applicant Email	studio@zpaaia.com
		Linked AP/Project Nos.	
SDOT Project No			

For detail zoning information, click the on the King County APN number above, or visit http://web1.seattle.gov/dpd/parceldata/ to find zoning details about your address.

PASV Report

Contact: Matthew S Recker, (206) 233-5034, Matt.Recker@seattle.gov

ECA Mapping Unit and Type

Non-ECA

Existing ROW Conditions 26TH AVE NE

Street conditions:

Concrete paving

Curb conditions:

Curb adjacent to site

Concrete

Approximate curb height: 4-5 inches

NE BLAKELEY ST

Street conditions:

Asphalt paving

Curb conditions:

Curb adjacent to site

Concrete

Approximate curb height: 4-5 inches

Potential Impacts to Seattle Parks Property

No parks property in vicinity

Tree Protection

Trees greater than 6 inches in diameter are present on the site but not shown on the site plan. Show the dripline of 1) **all** trees on the site, 2) adjacent trees that encroach on the site that are greater than 6 inches in diameter and 3) **all** trees located in the adjacent ROW. Include common and scientific names for all trees shown. See Director's Rule 16-2008 and CAM 242.

Construction Erosion Control

All projects with earth disturbance, regardless of size, require temporary and permanent stormwater control in accordance with the Construction Stormwater Control Technical Requirements Manual (DR 16-2009, Volume 2). The Stormwater Control Best Management Practices (BMPs) noted below can be found on the Construction Stormwater Control (CSC)/Post Construction Soil Amendment Plan or in the Construction Stormwater Control Technical Requirements Manual. Both are available online and from DPD's Public Resource Center.

Show the following on the CSC/Post Construction Soil Amendment Plan:

Place compost socks, compost berms, filter fabric fencing, straw bales, straw wattles, or other approved perimeter control BMPs to eliminate construction stormwater runoff.

Show the location of a stabilized construction access to the site; show methods to eliminate uncontrolled conveyance of mud and dirt into the right of way (ROW).

Place silt-trapping inserts in receiving catch basins located within 10 feet of construction entrance.

Cover bare soil with compost blankets, straw, mulch, matting, or other approved equal to control construction stormwater runoff.

Cover stockpiles and bare slopes with tarps, matting compost blankets or other approved equal to control construction stormwater runoff.

A temporary erosion and sedimentation control (TESC) First Ground Disturbance inspection is required before any ground disturbance related to this permit, including demolition, tree cutting, clearing, grubbing, and grading. After your permit is issued, schedule an inspection by calling (206) 684-8900 or online at: http://web1.seattle.gov/DPD/InspectionRequest

Inspectors Notes

Site slopes down gently to south and west. Moderately steeper slopes near east and north property lines. Specify locations and depths of proposed excavation.

Seattle City Light Requirements

Contact: Ray Ramos, (206) 615-1193, ray.ramos@seattle.gov

Street/Alley Requirements 26TH AVE NE

Working Clearance: State law requires construction workers, their tools, machinery, equipment, and materials to maintain a 10-foot clearance from power lines. Review WAC 296-24-960. Transmission lines require greater clearance. To work near power lines, notify SCL well in advance to de-energize and ground the lines, or relocate the lines temporarily. This SCL work is done at the project's expense. There is an overhead high voltage line along the east side of 26th Ave NE.

NE BLAKELEY ST

10' Clearance from Structures: 10-ft horizontal clearance required between power lines and permanent structures. Review DPD CAM 122, Electric Utility Clearance Requirements, and SCL Construction Guideline D2-3 (http://www.seattle.gov/Light/engstd/Docs/ConStd/d23.pdf) Changes to SCL's system to meet clearances are done at the project's expense. There are overhead high voltage lines along the north side of NE Blakeley St.

Working Clearance: State law requires construction workers, their tools, machinery, equipment, and materials to maintain a 10-foot clearance from power lines. Review WAC 296-24-960. Transmission lines require greater clearance. To work near power lines, notify SCL well in advance to de-energize and ground the lines, or relocate the lines temporarily. This SCL work is done at the project's expense. There are overhead high voltage lines along the north side of NE Blakeley St.

An SCL engineer will require scaled building elevation drawings to determine clearances. Please submit an extra set of plans at DPD intake.

Other requirements: The existing electrical service to the restaurant business is underground. Contact your Electrical Service Representative to coordinate service removal prior to demolition.

Other Requirements

• For new service, an Application for Electric Service must be submitted to Seattle City Light. Please contact the Electric Service Representative for your area several months before new service is required to determine your electric service design, service location and what kind of service is available at the building site. The Electrical Service Representative should also be contacted to coordinate electrical details with demolition and temporary power for construction. Your Electrical Service Representative is: Elifonso Leal, 206-684-4988, elifonso.leal@seattle.gov

DPD Drainage Requirements

Contact: Kevin Donnelly, (206) 684-5051, Kevin.Donnelly@seattle.gov

The following requirements are based on the current stormwater and side sewer codes. Major updates to these codes are expected in the fourth quarter of 2009.

Existing Public Drainage Infrastructure

Combined sewer main location: 26th Ave NE

Combined sewer main size: 30-inches

Drainage

The drainage point of discharge (SMC 22.802.015.C.1) is located at: Combined sewer.

Flow Control Compliance

All new, replaced, and disturbed topsoil shall be amended with organic matter per rules promulgated by the Director prior to completion of the project to improve onsite management of drainage water flow and water quality per SMC 22.805.020.E. Refer to CAM 531, Post Construction Soil Management. For projects with 5,000 square feet or more of new plus replaced impervious surface, a comprehensive drainage control plan and construction stormwater control plan shall be prepared by a licensed engineer.

Parcel-based projects with 7,000 square feet or more of land disturbing activity or 2,000 square feet or more of new plus replaced impervious surface must implement green stormwater infrastructure to infiltrate, disperse, and retain drainage water onsite to the maximum extent feasible without causing flooding, landslide, or erosion impacts per SMC 22.805.020.F. Refer to Director's Rule 19-2009 - Green Stormwater Infrastructure - Requirements for All Projects and Director's Rule 17-2009 - Stormwater Manual Vol. III - Stormwater Flow Control and Water Quality. Submit a GSI Calculator per DR 19-2009.

Water Quality

This project site discharges to a water body that requires basic treatment (SMC 22.805.050 B). Based upon the information provided on the Preliminary Application Form pertaining to existing and proposed impervious surfacing this project shall: provide a basic treatment facility that treats the required runoff volume or flow rate from pollution generating surfaces (SMC 22.805.090 B1, B2).

Permanent and Temporary Dewatering

The footing drain (if part of building plan) point of discharge (DPD DR 3-2006/SPU DR 02-06 VII.H) is located at the following: Combined system.

DPD Land Use Code Requirements

Contact: Lucas J DeHerrera, (206) 615-0724, <u>lucas.deherrera@seattle.gov</u>

Street Requirements

Based on the scope of the proposed project, the following street improvements are required per Chapter 23.53 of the Seattle Municipal Code. Please review Right-of-Way Improvements Manual for design criteria (http://www.seattle.gov/transportation/rowimanual/manual/). Show required street improvements on your "enhanced site plan" at DPD permit application intake. If an SDOT Street Improvement Plan (SIP) is required, please list SDOT project number and SDOT contact name on the enhanced site plan. Street Improvement Plans must be accepted by SDOT prior to DPD permit application intake.

26TH AVE NE

Street trees shall be provided in the planting strip according to Seattle Department of Transportation Tree Planting Standards. Contact SDOT Urban Forestry (for residential projects: (206) 684-TREE; for all others: (206) 684-5693), to determine species of tree and standards of planting. Please add a note to the site plan showing size, location and species of tree to be planted.

http://www.seattle.gov/transportation/treeplanting.htm.

Landscaping is required to be installed in the planting strips in the right-of-way. Contact SDOT Urban Forestry to determine species of landscaping and standards of planting. For residential projects, call (206) 684-TREE; for all others, call (206) 684-5693). Please add a note to the site plan showing size, location and species of shrubs and groundcover to be planted.

Any planting proposed within the ROW must be reviewed and approved by DPD and SDOT. See SDOT Street Use for early design guidance. Apply for SDOT SIP Design Guidance to obtain SDOT 60% complete SIP approval (see SDOT CAMS 2211 and 2213).

NE BLAKELEY ST

New structures must be designed to accommodate future right-of-way improvements. To ensure that driveways and pedestrian access points are designed to match these future street improvements, please use the Building Grade Calculator, which can be found at

http://www.seattle.gov/transportation/gradesheetintro.htm

Because full street improvements are not being required for this project, or the project qualifies for a reduced street improvement, a no-protest agreement is required. This form can be found at

http://www.seattle.gov/dpd/static/Covenant_Consenting_LID_LatestReleased_DPDS_006060.pdf

Street trees shall be provided in the planting strip according to Seattle Department of Transportation Tree Planting Standards. Contact SDOT Urban Forestry (for residential projects: (206) 684-TREE; for all others: (206) 684-5693), to determine species of tree and standards of planting. Please add a note to the site plan showing size, location and species of tree to be planted.

http://www.seattle.gov/transportation/treeplanting.htm.

Landscaping is required to be installed in the planting strips in the right-of-way. Contact SDOT Urban Forestry to determine species of landscaping and standards of planting. For residential projects, call (206) 684-TREE; for all others, call (206) 684-5693). Please add a note to the site plan showing size, location and species of shrubs and groundcover to be planted.

Existing curbcuts that will no longer be used are required to be removed, and the curbline reinstalled, per SDOT standards.

Any planting proposed within the ROW must be reviewed and approved by DPD and SDOT. See SDOT Street Use for early design guidance. Apply for SDOT SIP Design Guidance to obtain SDOT 60% complete SIP approval (see SDOT CAMS 2211 and 2213).

A appproximately 6.5' foot setback is required.

Land Use

Based on the project scope and/or location of environmentally critical areas on the development site, SEPA may be required. See CAM 208 for more details.

Design Review is required; see CAM 238 for more details. Departures from development standards should be identified as early as possible in the application process.

Other Requirements: ACU to continue non conforming parking in SF zone, see notes to applicant (DPD).

Other Requirements

A presubmittal conference is required before to submitting an application. Details for preparing and submitting a presubmittal request form can be found at our Web site (http://www.seattle.gov/dpd/Publications/Forms/Building_Permit/default.asp).

SDOT Requirements

Contact: Leo Kaarrekoski, leo.kaarrekoski@seattle.com

The City of Seattle's Right-of-Way Improvements Manual (ROWIM) and SDOT's Street & Sidewalk Pavement Opening and Restoration (PORR) Director's Rule 2004-02 may be accessed from SDOT's Street Use website at: http://www.seattle.gov/transportation/stuse_docs.htm. Whenever possible, specific reference notation for these two design documents is noted next to the design characteristics below. Be advised that these specific section and chapter references are provided as preliminary guidance only and are not comprehensive in scope.

Street Improvement Requirements NE BLAKELEY ST

Tree protection: Removal of trees in the public right-of-way (ROW) is prohibited. Projects must be designed to accommodate existing trees in the ROW. Exceptions to this policy require review and approval by SDOT Urban Forestry. For residential projects, call (206) 684-TREE; for all other projects, call (206) 684-5693. Contact SDOT Urban Forestry immediately if street trees you are proposing to remove street trees. If an exception from street tree removal is not granted, the project will need to be redesigned to preserve street trees.

SPU Requirements

Contact: Susie Larson, susie.larson@seattle.gov

Flow Control Compliance

All new, replaced, and disturbed topsoil shall be amended with organic matter per rules promulgated by the Director prior to completion of the project to improve onsite management of drainage water flow and water quality per SMC 22.805.020.E. Refer to CAM 501. For projects with 5,000 square feet or more of new and replaced impervious surface, a comprehensive drainage control plan shall be prepared by a licensed engineer.

Water Availability

Contact: K Younge, (206) 684-5975, Karen. Younge@Seattle.Gov

Your water availability assessment has been approved.

Water Availability Certificate reference number: 20100048 Water Availability Certificate status: Approved with No Changes

Prepared by: Melissa Hill

Existing Water System Information

Proximity of nearest fire hydrant is: 165 feet E of property. Meets standards.

Water Main:

Size: 12 inches Material: Cast Iron Class: 150

StandardAbutting

Water Main is available to serve in: NE Blakeley Street Distance of main to N margin of street is 36 feet.

Public ROW width is 60 feet.

landmarks and historic preservation.

Water Service(s):

Size: 1" Material: Copper

Other Requirements

Owners of residential property occupied by a tenant who will be displaced by housing demolition, substantial rehabilitation, change of use, or removal of use restrictions may need to obtain a Tenant Relocation License. Refer to DPD CAM 123, Seattle's Tenant Relocation Assistance Ordinance, for further information and instructions or call (206) 684-7979.

If your project involves additions or modification to or demolition of an existing building that contains four or more dwelling units or 4,000 square feet or more of non-residential area, and the building is a designated historic landmark or is 50 years old and meets the criteria set forth in SMC 25.12 for landmark designation, SEPA is required. Please contact the Department of Neighborhoods at (206) 684-0228 or www.seattle.gov/neighborhoods/preservation to determine if your building is a designated landmark of if a referral is necessary to determine if the building meets the criteria in SMC 25.12. Refer to CAM 208 for information regarding the application requirements for a SEPA review and CAM 3000 for information regarding

Applicant Next Steps

- 1. Please review the requirements set forth in this report.
- 2. Use Client Assistance Memos (CAMs), checklists and standards, and 5 Steps for a Successful DPD Application Submittal (available on the DPD website) for additional information.
- 3. Call or e-mail the appropriate contact if you have any outstanding questions.
- 4. If a SIP is required, you must submit it to SDOT to screen for acceptance a minimum of five days prior to DPD construction intake. DPD will not accept your application until this has been done.
- 5. Use the Seattle City Light website to obtain a range of information and services including the Requirements for Electric Service Connection (RESC), electric service applications and guidelines (http://www.seattle.gov/light/newconstruction/).
- 6. Contact an Electric Service Representative for your electrical service design and connection questions:

North of Denny Way (206) 615-0600

South of Denny Way (206) 386-4200

Large Commercial & Industrial (206) 233-7177

Service Applications (206) 233-APPS (2777)

- 7. If you have additional questions or need additional help, you may request a pre-submittal conference. For more information, call (206) 684-8850 or go to DPD's website for a copy of the pre-submittal conference application and instructions (http://www.seattle.gov/dpd/Publications/Forms/Building_Permit/default.asp).
- 8. When all issues have been addressed, you may schedule an intake appointment with DPD. Please bring a copy of this report.

The requirements and determinations set forth in this document are based on the following:

Details provided by the applicant on the preliminary application form and site plan submitted to DPD. If project criteria are changed before your SDOT SIP is designed and/or before your DPD intake, the requirements in this report are subject to change.

Current municipal codes and ordinances, which may be subject to change. If there are code changes prior to your DPD intake, the project must meet the new code requirements.

The scope of your proposed project as described in the preliminary application form. Additional street improvement requirements may be triggered if a permit application for a development project on adjacent property is also undergoing review.